

ASHP SOAK-AWAY



This unique pre-bagged geo textile soakaway is used to safely dispose of the condensate from all domestic sized air source heat pumps where drain routing is not available. The volume of condensate created from an air source heat pump up to 16kW can be between 10-15 litres per hour up to 2000 litres per year.

CAPACITY - 10-15 LITRES PER HOUR

FEATURES


- Alternative method to condensate removal disposal and suitable for all models/brands of air source heat pumps
- Made from pre-bagged geo-textile material to prevent soil ingress
- Pre filled with lightweight granules




SHOWING THE INSTALLATION BELOW GROUND OF THE ASHP SOAK-AWAY.




USING THE SOAK-AWAY PREVENTS THE CONDENSATE FROM FLOWING ONTO PATHS AND FREEZING - CAUSING A SLIP HAZARD.




1. IDENTIFY ROUTE OF CONDENSATE DRAIN FROM ASHP AND BEST LOCATION FOR POSITION OF SOAKAWAY.




2. SOAKAWAY SHOULD BE AT LEAST 600MM FROM THE WALL TO AVOID CAUSING DAMP TO THE FOOTINGS.




3. DIG A HOLE MINIMUM 500MM DEEP X MINIMUM 400MM DIAMETER.



4. INSET THE SOAKAWAY BAG WITH INLET HOLES FACING THE PROPERTY.



5. FOR FLOOR-MOUNTED ASHP FIT THE PIPEWORK FROM THE ASHP INTO THE SOAKAWAY BAG



6. FOR WALL-MOUNTED ASHP FIT THE PIPEWORK FROM THE ASHP INTO THE SOAKAWAY BAG

Part code	No of poles	Inlet	Diameter	Height
ASHP-SOAK	Air source heat pump soakaway - pre bagged geo textile with rubber chippings	32mm	400mm	400mm

DRAINAGE ASHP SOAK-AWAY

Condensate drainage solutions

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global